



Magnesia metallurgical flux FluMag M[®]

Description	Highly effective magnesian metallurgical flux with trademark "Flumag" is a lump (not briquetted) roasting free fireproof material. Flux produced from natural mineral brucite by selective extraction followed by X-ray radiometric separation in chemical composition and separation by fractional composition.	
Application	Used for improving of slag formation and correction of magnesium oxides in the slag during steelmaking in converters, namely for forming of wear resistant slag scull on the lining of the converter.	
Chemical and Physical properties	Indicator	Content
	MgO/Mg(OH) ₂ %	58,0/84,1 min.
	SiO ₂ , %	6 max.
	CaO, %	5 max.
	Fe ₂ O ₃ , %	0,5 max.
	S, %	0,03 max.
	Loss of Ignition (LOI)	35 max.
	Particle Size distribution, %:	
	0 – 10 mm	>95%
Storage:	The shelf life is 5 years from date of manufacturing, while maintaining the tightness of packing	
Packing:	in bulk, big bags	
Security:	refers to low-hazard substances; fire - and explosion-proof, non-toxic	
Transportation:	transported by all modes of transport in accordance with the rules of transportation of goods that operates in this mode of transport	

115093, Russia, Moscow,
Lusinovskaya str, 36 bid. 1
Tel: + 7(495) 789-65-30
info@magminerals.ru;
www.magminerals.ru



R U S S I A N
M I N I N G C H E M I C A L
C O M P A N Y